




- 1-Coolant inlet (G1/2") (3+4 bar) (6-8 L/min.)
- 2-Coolant outlet (G1/2")
- 5-Electric connection
- 3Phases motor - Earth
- 7-Front-side pressurization filtered (5µm)
- (1-1.5 bar) (G1/8")
- 15-Outlet encoder's cables (Gel 2444 KN)
- Motor thermal switch (N°1 PT 1000)

Grease Bearings Lubrication
Coolant Capacity = 3000 Watt



- 1 white A+
- 2 brown A-
- 3 grey Ref+
- 4 not connected
- 5 not connected
- 6 not connected
- 7 not connected
- 8 white-brown thermal switch PT 1000
- 9 white-brown thermal switch PT 1000
- 10 red -SV Dc
- 11 Pink A-
- 12 Pink A+
- 13 white Ref-
- 14 not connected
- 15 blue 5V sensor
- 16 green 5V sensor
- 17 not connected

SPEED	RPM	550	2100	3000
FREQUENCY	Hz	37	140	193
POWER (S1)	KW	18.5	18.5	18.5
TORQUE (S1)	Nm	321	84	61
TENSION (S1)	V	131	380	380
CURRENT (S1)	A	112	30	58



Asynchronous motor: 8 poles Runout taper 0.002mm

Peron Speed
SUBJECT: PSI TA-300
CUSTOMER: ASA 8

Sheet: 1/1 Dls. n° 3768-00 DATE: 02/07/2021