




- 1-Coolant inlet (G1/2") (3÷4 bar) (8÷10 L/min.)
- 2-Coolant outlet (G1/2")
- 5-Elattric connection
- 3Phases motor - Earth
- 7-Front-side pressurization filtered (5µm) (1-1.5 bar) (G1/8")
- 15-Outlet encoder's cables (Gel 2444 KN) -Motor thermal switch (N°1 PT 1000)

Grease Bearings Lubrication
Coolant Capacity = 3600 Watt



- 15
- 1 white A+
 - 2 brown A-
 - 3 grey Ref+
 - 4 not connected
 - 5 not connected
 - 6 not connected
 - 7 not connected
 - 8 white-brown thermal switch PT 1000
 - 9 white-brown thermal switch PT 1000
 - 10 red +5V DC
 - 11 Pink A-
 - 12 Pink A+
 - 13 Valtio B-
 - 14 Valtio B+
 - 15 not connected
 - 16 blue OV
 - 17 not connected
- screen on carcass

SPEED	RPM	550	1000	3500
FREQUENCY	Hz	37	196	233
POWER (S1)	KW	13	23	23
TORQUE (S1)	Nm	220	220	63



Synchronous motor: 8 poles Runout taper: 0.002mm

Peron Speed
SUBJECT : PSI TA-302
CUSTOMER : ASA 8

Sheet:1/1 Dls.n°2037-00-01 DATE : 02/07/2021